



US009560751B2

(12) **United States Patent**  
**Huitema et al.**

(10) **Patent No.:** **US 9,560,751 B2**  
(45) **Date of Patent:** **Jan. 31, 2017**

(54) **SUPPORT STRUCTURES FOR AN ATTACHABLE, TWO-DIMENSIONAL FLEXIBLE ELECTRONIC DEVICE**

H05K 2201/041; H05K 2201/042; H05K 2201/043; H05K 2201/045; H05K 2203/167; H05K 7/1454; H01R 23/7042; H01R 23/7047; H01R 12/71  
(Continued)

(71) Applicant: **POLYERA CORPORATION**, Skokie, IL (US)

(72) Inventors: **Hjalmar Edzer Ayco Huitema**, Belmont, CA (US); **Philippe Inagaki**, Skokie, IL (US)

(73) Assignee: **Polyera Corporation**, Skokie, IL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/850,327**

(22) Filed: **Sep. 10, 2015**

(65) **Prior Publication Data**

US 2016/0037625 A1 Feb. 4, 2016

**Related U.S. Application Data**

(63) Continuation of application No. PCT/US2014/072172, filed on Dec. 23, 2014.  
(Continued)

(51) **Int. Cl.**  
**H05K 1/14** (2006.01)  
**H05K 1/02** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **H05K 1/028** (2013.01); **G09F 9/301** (2013.01); **G09F 21/02** (2013.01); **G09F 21/026** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... H05K 1/14; H05K 1/142; H05K 1/145; H05K 1/147; H05K 5/0291; H05K 1/144;

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,834,376 A 5/1989 Steinberg  
5,065,376 A 11/1991 Choulat  
(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 101180669 A 5/2008  
CN 101180864 A 5/2008  
(Continued)

**OTHER PUBLICATIONS**

“3M Flexible Transparent Touchscreen Concepts” video located on the Internet at <[http://www.youtube.com/watch?v=kCZz4jFok\\_o](http://www.youtube.com/watch?v=kCZz4jFok_o)> (uploaded Jan. 6, 2011).

(Continued)

*Primary Examiner* — Binh Tran

(74) *Attorney, Agent, or Firm* — Karen K. Chan

(57) **ABSTRACT**

A dynamically flexible article or device, such as an armband, includes a flexible electronic component, such as a flexible electronic display, and a flexible support structure coupled to the flexible electronic component, wherein the flexible support and the flexible electronic component are flexible along two dimensions to thereby be able to conform to a complex curved surface. The flexible support includes bending limiting structure that constrains bending of the flexible electronic component to prevent undesirable bending.

**18 Claims, 36 Drawing Sheets**

